Clearly Better

The New eSpring™ Water Purifier:

See the difference for yourself!	The new eSpring Water Purifier	Current eSpring Water Treatment System
Contaminant Claims	• Micro-plastics • PFOA & PFOS • 19 Pharmaceuticals • 1, 2, 3-TCP certified	• UV-susceptible cyst (Only giardia & cryptosporidium) • 9 pharmaceuticals • 1, 2, 3-TCP verified
Total Contaminant Claims	170+	140
UV-C LED Claims	UV-C LEDs effectively destroys up to: • 99.9999% of bacteria • 99.99% of viruses • 99.9% of waterborne cysts	UV lamp effectively destroys up to • 99.9999% of bacteria • 99.99% of viruses • 99.9% of waterborne cysts
UV Light	• Powered by UV-C LED technology • Up to 10-year life • Amway™ first with UV-C LED water treatment system certified by NSF Int'l. to NSF/ANSI Standard 55 for Class B microbial reduction	• Lasts up to one year (average) • Annual UV lamp disposal
eSpring e3 Carbon Filter	• 5,000 L or one-year life	• 5,000 L or one-year life.
Filter Change Experience	• Filter changes in 2-1-0 - 2 minutes - 1 time per year (average) - 0 tools required • No tubing disconnection	• Requires tubing disconnection • Filter requires specific orientation • Tube removal tool needed
Connectivity through the new Amway™ Healthy Home app	• Filter change alerts • Order filters directly from the app • Water usage stats • Automated software updates • Product information • How-to videos • Product registration	• Not connected • No app available
Environmental Benefits	• One e3 carbon filter (5,000 L/year) = 10,000 500 mL plastic bottles of water • Less electronic waste • No annual UV lamp disposal	One filter cartridge = 10,000 bottles of water
Footprint (with tubing)	16% smaller footprint 25.5 cm (L) x 14 cm (D), 357 sq. cm	17 cm (L) x 25 cm (D), 425 sq. cm
Power Consumption During Operation	45W – consumes 25% less power	60W
Display	Display illuminates only as water is flowing	Bright blue/red lights (always on)
RFID System	• Latest technology • Optimized design position (avoids RFID issues)	• Older technology • Non-standard application
UV Status Monitoring	Electrical power measurement directly monitors status of UV-C LED (avoids red phone, red cup issues)	Optical sensor detects UV lamp operation
Rated Pressure	15-100 PSI	15-125 PSI
Rated Water Temperature	4.4 C-30 C	4.4 C-30 C
Limited Warranty	Five-year warranty	Standard two-year warranty

eSpring™